

Customer's address (Rubber Stamp - black)

## Inquiry/Order Form for EV Valves

Order-No: \_\_\_\_\_ Date: \_\_\_\_\_

Ordered by: \_\_\_\_\_ Telephone: \_\_\_\_\_

Blain Hydraulics GmbH  
Pfaffenstr. 1  
74078 Heilbronn / Germany  
Tel.: 07131/28210  
**Fax.: 07131/282199**  
**E-Mail: info@blain.de**

VALVE SPECIFICATIONS	Pos. 1	Pos. 2	Pos. 3	Pos. 4	Pos. 5	Pos. 6	Pos. 7	Pos. 8	Pos. 9	Example
Client.No.										
Delivery Required (Week)										42
Quantity										2
<b>1) Port Size 2) Typ 3) Flow Guide</b>										3/4" 100/05
<b>4) Solenoid Voltage AC or DC</b>										110 DC
<b>5) Pump (lpm - gpm)</b>										100
<b>6) Empty Car Pressure (bar - psi static)</b>										30
Loaded Car Pressure (bar - psi static)										46
Piston Diameter (mm - inch)										1x70
Car Speed up/down (m/s - feet/min)										0.6 / 0.8

OPTIONS										
Pressure Compensated Bypass	CU									X
Pressure Compensated Down	CX									
Hand Pump built-on	HP									X
Emergency Lowering, 12/24 V	EN									12 V DC
Slack Rope Valve	KS									X
Extra Down Valve Manual	HX									
Extra Down Solenoid	MX									
Manual Lowering for MX	HM									
Slack Rope Valve HX or MX	KS									
CSA Coils	CSA									
Coils with Diode Lamps	LM									
Ball Valve (select size)	BV									BG 1 1/2"
Pressure Switch 10 - 100 bar	DH									
Pressure Swich 1 - 10 bar	DL									X

**1) 2) 3) 4) or 1) 2) 4) 5) 6)** have to be specified. Further details allow us to optimise the preadjustment of the valves.